
### ALEX LIFESON ES-LP SIGNED ARTIST PROOF #2

















### **GIBSON DESCRIPTION OF PRODUCTION MODEL**


http://www.gibson.com/Products/Electric-Guitars/2016/Memphis/Alex-Lifeson-Signature.aspx

## Alex Lifeson ES-Les Paul



\$3,999

Gibson Memphis honors the world renowned guitarist of Rush with the popular new Les Paul-meets-ES-335 hybrid, made to the specifications of Alex Lifeson himself. Premiere tone is produced thanks to quarter-sawn, thermally engineered Adirondack spruce bracing and a thermally engineered Mahogany centerblock, two PAF-like MHS humbuckers, matched potentiometers, historic truss rod, titanium bridge saddles, a bone nut and more, while rolled neck binding delivers a sublimely comfortable playing feel.




Thermally engineered braces and

centerblockThermally engineered Adirondack spruce braces secured to maple top with hot hide glue.			
Thermally engineered mahogany centerblockLarge block inlaysElegant large mother of pearl block inlays			
in a dark Richlite fretboard give a top of the line appearance. Rolled fingerboard bindingBy "rolling" or			
"breaking" the binding at the fingerboard edge we create a softer playing feelHistoric truss rodOur historic			
truss rod has no tube, a proven known to enhance the guitar's resonance and sustainMHS			
pickupsMemphis Historic Spec humbuckers are our closest yet to the hallowed PAF of the late '50s and			
early '60sMatched potentiometersMatched 550K potentiometers coupled with 'orange drop' capacitors			
contribute to high definition toneBone nutBone has been preferred for years on high-quality guitars for its			
contribution to outstanding resonance and sustain High-gloss nitro finishOur labor-intensive nitrocellulose			
finishing process yields a lustrous high-gloss look			

- **Body:** Thermally engineered Adirondack spruce braces and mahogany centerblock
- Fingerboard: Richlite with large block mother of pearl inlays
- Binding: Rolled for superb playing comfort
- Truss rod: Historic truss rod
- **Pickups:** MHS humbuckers
- Potentiometers: Matched 550K potentiometers
- Nut: Genuine bone
- Finish: High-gloss nitrocellulose lacquer

## Body



### Тор

Wood Species: Maple, Poplar, Maple	
Pieces:	3-Ply
Grade:	Plain
Binding:	7-Ply (W-B-W-B-W-B-W)

### Back

Wood Species:	Maple, Poplar, Maple
Pieces:	3-Ply
Density:	Plain
Binding:	3-Ply (W-B-W)

### Rims

Species Wood:	Maple, Poplar, Maple	
Pieces:	3-Ply	
Grade:	Plain	
Weight		
Weigh	t Relief:	Thermally Engineered ES-LP Center Block
Average Weigh	nt (body only):	1.3925 kg / 3.070 lbs.

### Materials Used

Glue:	Hot Hide glue for braces and centerblock, Franklin Titebond 50 for rims
Etc.:	Thermally Engineered Adirondack Spruce braces
Tonal, Resonant, and/or Technical Effect:	The sound waves resonate within the hollow airspace of the Maple veneered Body, around the F-holes, and throughout the solid glue joints.

### Body Contour Carve: ES-LP (Semi-Hollow)

## Neck









Neck Wood Species: Mahogany Pieces: 1

Details

Truss Rod: Historic Profile: Rounded "C" Thickness at Fret 1: 21.59 mm / .850" Thickness at Fret 12: 24.13 mm / .950" Other Materials: Franklin Titebond 50 Average Weight: 544.31 gm / 1.2 lbs

### Peg Head

Туре:	SP-2
Inlay:	Mother of Pearl "Split Diamond"
Peg Head Binding:	5-Ply (W-B-W-B-W)
Logo:	Mother of Pearl "Gibson"
Silkscreen:	None
Headstock Angle:	17 degrees
Tonal, Resonant, and/or	The rounded neck provides an ergonomic feel and
Technical Effect:	the mahogany adds a rich tonal quality

### Neck Fit

Joint Angle:	4 degrees
Joint Angle Tolerance:	0
Туре:	Mortise and Tenon
Adhesive:	Hot Hide Glue
Gauges Used:	Pitch Height Gauge
Nut	
Style:	White
Material:	Bone
Width:	4.2863 cm / 1.6875"
Slots:	E: 1.2268 mm / 0.0483 inches A: 0.9601 mm / 0.0378 inches D: 0.6934 mm / 0.0273 inches G: 0.4534 mm / 0.01785 inches B: 0.3467 mm / 0.01365 inches e: 0.2667 mm / 0.0105 inches

### Fingerboard

Wood Species:	Richlite
Pieces:	1
Shade:	Dark

### **Fingerboard Details**

Radius:	30.48 cm / 12 "
Frets:	22
Nut/End of Board:	4.2863 cm / 1.6875" @ nut, 5.2375 cm / 2.062" @ end of board
Scale:	62.865 cm / 24.75"
Binding:	White
Side Dots (Color):	Black

### **Fingerboard Inlays**

Style:	Full Block
Material:	Mother of Pearl
<b>Dimensions:</b>	22.479 mm x 27.6352 mm / 0.885" x 1.088"
Average Weight:	136.0777 gm / 4.800 oz

## Finishes



**Classic White** 

Color Code:	CW
Surface Texture:	Smooth/ Hi Gloss 90 Sheen Lacquer - Finished in V.O.S.
Filler:	Natural
Sealer:	1-1.5 mils
Тор:	Classic White
Top Coat:	Hi Gloss Lacquer/ 90 Sheen 7-8 mils
Scraped:	Fingerboard Sides, Body and Nut

## **Electronics**





### Pickups Rhythm

Style: Winds/Coil: Screw side/Slug side:

Style: MHS Humbucker

5100/4900

Lead

MHS Humbucker

5400/5200

Material of Wire (gauge):	Enamel (42)	Enamel (42)
	6.6294 cm x 1.7272 mm / 2.61" x 0.68 "	6.6294 cm x 1.7272 mm / 2.61" x 0.68 "
, i i i i i i i i i i i i i i i i i i i	ABS	ABS
Coil Winding Process:	Scatter Wound	Scatter Wound
Pole Piece Material:	Gold plated steel	Gold plated steel
Pole Piece Position from Nut:	47.4218 cm / 18.670"	59.5173 cm / 23.432 "
Slug Material:	Nickel plated steel	Nickel plated steel
Slug Dimensions (diameter x length):	4.7498 mm x 1.24206 cm / 0.187" x .489"	4.7498 mm x 1.24206 cm / 0.187" x .489"
Magnet Material:	Alnico III	Alnico II
Magnet Position from Nut:	48.26 cm / 19"	58.42 cm / 23"
Magnet Dimensions:	6.35 cm x 1.27 mm / 2.5" x 0.5"	6.35 cm x 1.27 mm / 2.5" x 0.5"
Polarities:	Screw side is the south pole of magnet	Screw side is the south pole of magnet
Cover:	Gold plated	Gold plated
Qfactor:		3.2
ResistanceDC:	7526 ohms	7963 ohms
Resonant Frequency:	2859.84 Hz	2695.19 Hz

Historically accurate "Patent Applied For" replica with airy tone **Tonal & Resonant** and unbalanced coils. Slightly under wound. Historically Advancements: accurate "Patent Applied For" replica with airy tone and unbalanced coils. Slightly under wound.



Control Pocket Lead Assembly Volume

> Type: Peak Voltage: Range: Power Rating:

Resistance Tolerance: Minimum Resistance:

### Lead Tone

Type: Peak Voltage: Rhythm Volume CTS 550K Audio

1080V 0-550K 1/4 watt above 100K ohms 550K +/- 5% 50 ohms

### **Rhythm Tone**

CTS 550K Audio 1080V

	Range:
Power	Rating:

Resistance Tolerance: Minimum Resistance: 0-550K 1/4 watt above 100K ohms 550K +/- 5% 50 ohms

Capacitors:

Lead Value

**Rhythm Value** 

Orange Drop .022 mF Orange Drop .015 mF

## Hardware



# Tuning KeysStyle:Milk Bottle Grover RotomaticMaterial:Die cast alloyWeight:38.5554 gm / 1.36oz

### **Tuning Keys Details**

Tuning Ratio:	18:01
Gear Type:	Syncronized spur gear system
What is allowable turn:	+/- 4 degrees
Plating specs:	Gold
Part numbers:	430-14188 / 430-14189

### String Dimensions

- E: 1.1684mm / 0.046"
- A: 0.9144 mm / 0.036"
- D: 0.6604 mm / 0.026"
- G: 0.4318mm / 0.017"
- B: 0.3302mm / 0.013"
- e: 0.2540mm / 0.010"

### Bridge

Style:ABR with Titanium SaddlesMaterial:Die cast alloyPlating Specs:GoldPart number:430-10103Weight:54 gm / 1.9 oz

### **Dimensions of String Slots**

- E: 1.2268 mm / 0.0483 inches
- A: 0.9601 mm / 0.0378 inches

- D: 0.6934 mm / 0.0273 inches
- G: 0.4534 mm / 0.01785 inches
- **B:** 0.3467 mm / 0.01365 inches
- e: 0.2667 mm / 0.0105 inches

### Tailpiece

Style:	Lightweight Stop Bar
Compensated:	No
Material:	Aluminum
Plating Specs:	Gold
Part number:	430-11739 / 430-10930VL (Studs)
Weight:	113.3981 gm / 4.0 oz

### **Output Jack**

Style: 1/4" mono

### Jack Plate

Style:	Les Paul Square
Material:	ABS - Black
Part Number:	430-19385
Weight:	2.0 gm / 0.07 oz

### **Strap Buttons**

Material:BrassPlating Specs:NonePart numbers:430-19521Weight:2.268 gm / 0.080 oz

## Plastics





### **Pick Guard**

Style:Multi Ply Black Les PaulPart Number:380-12580

### **Truss Rod Cover**

Style: Black and white bell with engraved F-Hole Part Number: 430-19802

### **Knobs**

Style: **Black Top Hats** Part Number: 430-19669

**Dial Pointers** 

Yes/No: Yes

Control Plate(s) (Backplate Cover)

Style: N/A

Part Number: N/A

Control Plate(s) (SwitchPlate

Cover)

Style: N/A

N/A Part Number:

### Switch Washer

Black with hot stamp Style:

Part Number:

gold 430-19295

### Trim Rings

Style: Black Part Number: 440-13850

## Accessories



### Case

- Style: Hard Shell
- Color: Brown
- Strap Locks: No
  - Tools: None

### Manual: None

### COA/Other: Gibson Memphis Artist COA